

## Environmental Protection Agency

## § 405.116

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kilograms per 1,000 kg of BOD <sub>5</sub> input)		
BOD <sub>5</sub> .....	1.00	0.400
TSS .....	1.50	.600
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
English units (pounds per 100 lb of BOD <sub>5</sub> input)		
BOD <sub>5</sub> .....	0.100	0.040
TSS .....	0.150	.060
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

(b) For whey condensing plants with 300,000 lb/day or less of raw fluid whey input (less than 20,700 lb/day of solids or 14,160 lb/day of BOD<sub>5</sub> input).

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kilograms per 1,000 kg of BOD <sub>5</sub> input)		
BOD <sub>5</sub> .....	1.30	0.650
TSS .....	1.950	.975
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
English units (pounds per 100 lb of BOD <sub>5</sub> input)		
BOD <sub>5</sub> .....	0.130	0.065
TSS .....	0.195	.098
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

(c) For plants in the size range covered in paragraph (b) once-through barometric condenser water may be discharged untreated if the composite net entrainment is below 15 mg/l of BOD<sub>5</sub> for any one day and below 10 mg/l of BOD<sub>5</sub> as the average for thirty consecutive days.

[39 FR 18597, May 28, 1974, as amended at 60 FR 33935, June 29, 1995]

### § 405.113 [Reserved]

### § 405.114 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process waste-

water pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard
pH .....	No limitation.
BOD <sub>5</sub> .....	Do.
TSS .....	Do.

[40 FR 6435, Feb. 11, 1975, as amended at 60 FR 33935, June 29, 1995]

## § 405.115 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kilograms per 1,000 kg of BOD <sub>5</sub> input)		
BOD <sub>5</sub> .....	0.220	0.110
TSS .....	0.276	.138
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
English units (pounds per 100 lb of BOD <sub>5</sub> input)		
BOD <sub>5</sub> .....	0.022	0.011
TSS .....	0.028	.014
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

## § 405.116 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33935, June 29, 1995]